



KAMPERS 2M-series XHL



KAMPERS 2M-series XHL is a robust pump with extra shaft length resulting in more extensive sealing arrangements, such as double (cartridge) seals and gland packing. It is constructed horizontally with flanges inline on the sides and a built-on pressure relief valve on top. A foot heating system for steam, water or thermal oil is optional, as well as an electrical heating element. It is suitable for non-corrosive non-lubricating fluids.

Thanks to the wide range of sealing possibilities, the XHL is applied in tank storage, shipping and industry. The XHL offers the optimal solution should environmental requirements, safety regulations or fluid properties dictate

double sealing arrangements. It is self priming and can handle limited dry-running. Thanks to the inline flanges the piping can be constructed horizontally to meet height restrictions if necessary.

- Wide capacity range 2-900 m³/h
- Medium pressure range max 25 bar
- Medium temperature range <180°C
- Wide viscosity range 0,6-100.000 cSt
- Many sealing possibilities
- Horizontal with inline flanges
- Foot heating: steam, water, thermal oil or electric
- Pressure relief valve





2M XHL PUMPSIZE	OUTLINE & INSTALLATION DIMENSIONS																SHAFT DIMENSIONS				HEATING, LUBRICATION & DRAIN DIMENSIONS								WEIGHT		
	L0	L1	L2	L3	W1	W2	W3	W4	W5	W6	H1	H2	H3	H4	S	Z	d	L4	B	t	L5	H5	R1	R2	R3	R4	R5	R6	R7	Kg	
82	719	190	150	271,5	255	220	158	160	160	33,5	177	120	20	414	4	Ø14	Ø22	50	6	24,5	70	68	Rc1/2	Rp1/4	Rp1/4	Rp1/4	Rp1/4	Rp1/4	M14x1,5	M14x1,5	108
98	798	240	190	304	300	260	190	180	180	38,5	207	140	26	480	4	Ø18	Ø28	60	8	31	95	65	Rc1/2	Rp1/4	Rp1/4	Rp1/4	Rp1/4	Rp1/4	M14x1,5	M14x1,5	167
114	903	280	230	343	340	295	225	210	210	43,5	220	160	30	552	4	Ø18	Ø32	80	10	35	110	70	Rc3/4	Rc1/2	Rp1/4	Rp1/4	Rp1/4	Rp1/4	M14x1,5	M14x1,5	263
140	1066	350	290	393	380	325	240	240	240	54	270	180	32	624	6	Ø23	Ø42	80	12	45	145	80	Rc1	Rc1/2	Rp1/4	Rp1/4	Rp1/4	Rp1/4	M14x1,5	M14x1,5	366
166	1246	400	340	460	480	420	320	285	285	64	325	225	35	740	6	Ø23	Ø48	110	14	51,5	170	100	Rc1	Rc1/2	Rp1/2	Rp1/4	Rp1/4	Rp1/4	M20x1,5	M14x1,5	637
206	1498	470	400	558,5	560	500	380	365	330	80	385	260	36	830	6	Ø27	Ø60	120	18	64	200	110	Rc1	Rc1/2	Rp1/2	Rp1/4	Rp1/4	Rp1/4	M20x1,5	M14x1,5	798
268	1516	480	400	558,5	680	610	470	470	400	95	450	315	45	990	6	Ø30	Ø60	120	18	64	250	115	DN25	Rc1/2	Rp1/2	Rp1/4	Rp1/4	Rp1/4	M20x1,5	M20x1,5	1105

www.kampers.com